

3M Scotch-Brite™

Orange & Green Floor Pad

Ref 5000

For wet cleaning of protected or shiny floors

For high speed spray cleaning of protected floors



Technical data sheet

TD112

Date: August 2011

Supersedes: January 2007

Author : FG

Description:

The Scotch-Brite™ Orange & Green Floor Pad is a premium quality floor maintenance pad, made of high quality synthetic fibre, in an open textured non-woven construction. Polishing particles are dispersed throughout and bonded with a durable polymer coating.

Special Features:

- Specific fibre mix to ensure multiple contacts with the floor and a faster scrubbing action
- Non scratching/damaging protected floors
- Open textured construction for easier washing of pads after use, for longer coverage from each side and to resist clogging
- Consistent performance
- Durable pad..

Where and When to Use:

RPM	150-400	>400
Strip		
Deep cleaning		
Spray	XX	XX
Scrubber dryer	XX	
Buff	X	X

XX Designed for X suitable

Use Scotch-Brite™ Orange&Green Floor Pad for routine wet cleaning of shiny stone floors or protected floors.

It is also used for high-speed spray cleaning operation of protected floors at 500-1200 RPM.

Directions for Use:

1. Install a clean floor pad under the machine pad holder
2. Dust mop the area.
3. Wet scrub the area using detergent solution or spray clean using spray cleaning chemical
4. Remove pad and wash after use.

Maintenance of pad:

1. Remove from machine after each use and shake dust out of pads (after spray cleaning)
2. Rinse wash under tap water or machine wash every 5 uses.
3. Hang up for drying .

Note: machine washed floor pads will shrink about 20 mm after first washing cycle. Recommended washing-machine temperature is 40°C.

Performance Advantages:

Removes black marks on protected floors

Durability : 25 000 sqm at 1000 RPM in standard use (standard floor, appropriate maintenance)

Product Specifications:

Scotch-Brite™ Orange-Green Floor Pads consist of polyester fibre and synthetic polymer coating. They are not significantly

affected by water, detergents and cleaners normally used for floor maintenance.

Product Characteristics:

Colour: Orange & green
Marking: 3M logo and reference.
Thickness: 25.0 mm
Centre hole: Pre-cut at 85 mm
Weight: 1170 g/m²
Fibre type: Polyester

Aggressiveness (Schiefer Value):

Expected value for polishing operation: 0g
3M value : 0g

Packaging and labeling:

Packaging material made of 100% recyclable material.
Multilingual grey coloured label on each case.

Standard Sizes:

Standard and non-standard sizes available on demand.

Disposal Information:

Discard into appropriate container, for incineration, if available.
Packaging material: recyclable.

Origin:

Made in 3M USA. in an ISO 9001:2008 and ISO1 4001:2004 certified plant.