



GR1500 and GR3000

Graffiti Stain Removers

Technical Data

Technical Data Sheet - Date: July 2012

General Description :

3M Graffiti Removers are specifically designed for maximum effect, to remove aerosol spray paints, felt pen inks, emulsion paints, lipstick and crayon from their recommended surface type. GR1500 is formulated to remove safely and effectively graffiti from most plastic surfaces and from most painted or varnished surfaces without damaging or harming them.

GR3000 is formulated to remove graffiti effectively from brickwork and concrete surfaces.

Special Features :

- Liquid form allows a quick penetration and a fast breakdown of the graffiti.
- Low odour
- Uses biodegradable raw materials, does not contain aromatic, aliphatic or chlorinated solvents, very low environmental impact
- Neutralised with water.

Where and When to Use :

Use GR1500 on: Most Plastics, Plastic Laminates, Flat Unstressed Poly carbonate Sheeting, Clear Acrylic Surfaces, Some Vinyl, Gloss Painted Surfaces, Varnish Surfaces, Latex Paints.

Use GR3000 on: Brickwork, Concrete, Metallic Surfaces, Stainless Steel, Vitreous Enamel, Ceramic Tile.

Directions for Use :

1. For best results spray onto the graffiti and leave up to five minutes before agitating with a cloth or brush. Another method is to dampen a clean Scotch-Brite™ 350 or a 3M Scotch-Brite™ microfiber wipe such as Scotch-Brite™ 2010 High Performance cloth with the liquid. Dab and wipe off the graffiti, turning the cloth frequently to ensure the mark is not returned to the surface.
2. Wipe off any residue with a clean damp Scotch-Brite™ 350 or a 3M Scotch-Brite™ microfiber wipes such as Scotch-Brite™ 2010 High Performance cloth then rinse the surface, for best results wash with a mild detergent.
3. If preferred, apply the liquid with a soft brush then continue agitating to remove the graffiti.
4. Ensure that the surface is kept wet, if necessary re-apply the liquid. Wipe and rinse as above. Do not skip rinsing with water at the end of the job.

Notes :

Test on a small area prior to complete coverage to check for surface compatibility.

The graffiti removal action will stop once rinsed with water.

Product may have a limited effect on aged graffiti which may have already damaged the surface.

Shelf Life:

The shelf life is 3 years after manufacturing date for unopened containers.

Precaution Summary :

Refer to Material Safety Data Sheet for specific health hazards, first aid and precautionary information.

For GR1500

H332 Harmful if inhaled.
H319 Causes serious eye irritation.
H315 Causes skin irritation.

For GR3000

H319 Causes serious eye irritation.
H315 Causes skin irritation.

Product Specifications :

	GR1500	GR3000
Boiling point	>100°C	
Flash point	100°C	
Density	0.97	1.04

Building and Commercial Services

3M Belgium
Canadastraat 11, Haven 1005
2070 Zwijndrecht, Belgium